

## Datasheet BKK

### Composition

Fabric : Polyester fabric  
Coating : Double-sided, plasticized PVC  
Thickness : -

90 gr/m<sup>2</sup>  
250 gr/m<sup>2</sup>  
340 gr/m<sup>2</sup> max. - 5%

### Properties

		Length	Width	
Tensile strength	DIN53354	800 N/5cm	700 N/5cm	± 20 %
Elongation	DIN53354	20 %	30 %	± 25 %
Tear strength	DIN53356	30 N	35 N	± 25 %
Adhesion	DIN53357	> 50 N/5cm		
Impermeability to water	DIN53886	> 100 cm		
Colorfastness	ISO 105	> 6		
Cold resistance	DIN53361	< -25 °C		

### Washing instructions



Handwash

Clean with damp piece of cloth and household soap (solvent free).  
Don't fold and put the material away when wet.

### Remarks

Small differences in color and gloss are possible (hold recipe numbers separated).  
Reproducibility Color: unicolor < 1, printed < 1.5, dualcolor < 2 (Delta E CIE-lab 1976 D65).

Date: 26/9/2018

Datasheet date: 24/7/2018

ABN AMRO BANK: 47.37.10.978  
IBAN: NL94ABNA0473710978  
BIC: ABNANL2A

ING BANK: 903250  
IBAN: NL45INGB0000903250  
BIC: INGBNL2A

BTW/VAT: NL005840247B01  
Chamber of Commerce: 08036741

Our general terms and conditions are applied to all our offers, orders and agreements. A copy is available on request.



Management  
System  
ISO 9001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 3108622561